

Important Information About The WaterBoy Floral Watering Machine MODEL # WB M 3.5 Cube




INSTRUCTIONS:

- CAREFULLY UN BOX THE WATERBOY
- ATTACH THE SINK TO HOSE ADAPTER
Unscrew the aerator tip off your sink and screw on the Sink-to-Hose Adapter
- FILL THE WATERBOY
Attach the Swivel Fitting that's on the end of the ON/OFF Flow Control Valve to the sink. Turn Valve to the open position and turn water on.
- FILLING TIME: 2 MINUTES.** WHEN WATERBOY IS FULL
A) Shut off water, B) Turn off the valve,
C) Unscrew from sink
- ATTACH THE WATER WAND OR BREATHE FLOW CONTROL WAND
Screw Water Wand to Swivel end of Valve. Keep valve in OFF position.

CAUTION: DO NOT unscrew the Brass double female swivel off of the shut-off valve or it will leak and warranty will be void.

CAUTION: DO NOT Break or Remove seal. Releasing air from top chamber will disable the unit.




This is a 1/4 turn valve. DO NOT force past the off position or valve handle may snap off!



To adjust flow, with valve in the OFF position, use your fingers to PRESS on the Thumb Valve.



Slightly crack the flow valve. Flow starts off as a drip, continue until you adjustment is the way you like it.



Here's how it works! Normal water pressure the WaterBoy's unique tank! **IMPORTANT: DO NOT** break air cap seal on tank!

